



PVC WALL & DOOR PROTECTION

Featuring AM-Guard Antimicrobial
premium quality scratch-resistant
PVC cladding sheets


PVC WALL & DOOR PROTECTION COLOURS

AM-Guard Wall Protection sheets have a tough textured surface that is 20 times more scratch-resistant than standard PVC. Ideal for walls and doors in high-traffic areas where impacts are likely. Proven antimicrobial performance in healthcare, commercial and educational environments.




2MM WHITE

Sheet: 2mm AM-Guard PVC Wall Protection
Code: AM-G10/1W
LRV: 88
Finish: Textured




2MM PEARL

Sheet: 2mm AM-Guard PVC Wall Protection
Code: AM-G10/2P
LRV: 82
Finish: Textured




2MM IVORY

Sheet: 2mm AM-Guard PVC Wall Protection
Code: AM-G10/31V
LRV: 89
Finish: Textured



2MM BUTTERCUP YELLOW

Sheet: 2mm AM-Guard PVC Wall Protection
Code: AM-G10/4BY
LRV: 69
Finish: Textured




2MM ATLANTIC BLUE

Sheet: 2mm AM-Guard PVC Wall Protection
Code: AM-G10/5AB
LRV: 25
Finish: Textured




2MM MIDNIGHT BLUE

Sheet: 2mm AM-Guard PVC Wall Protection
Code: AM-G10/6MB
LRV: 10
Finish: Textured



2MM CEMENT GREY

Sheet: 2mm AM-Guard PVC Wall Protection
Code: AM-G10/7CEG
LRV: 65
Finish: Textured




2MM MIDWAY GREY

Sheet: 2mm AM-Guard PVC Wall Protection
Code: AM-G10/8MG
LRV: 37
Finish: Textured



2MM BATTLESHIP GREY

Sheet: 2mm AM-Guard PVC Wall Protection
Code: AM-G10/9BSG
LRV: 13
Finish: Textured



2MM CHARCOAL GREY

Sheet: 2mm AM-Guard PVC Wall Protection
Code: AM-G10/10CG
LRV: 8
Finish: Textured



To discuss your project requirements
email info@am-clad.com
or call **01274 020 331**

SPECIFICATIONS

SHEET DETAILS

2mm AM-Guard Wall & Door Protection

3050mm (10') x 1220mm (4')

Finish: Textured, scratch-resistant

Weight: 3.5 kg per m²

Service temp: -10°C to +60°C

Performance: Antimicrobial

PREPARING THE SURFACE

AM-Guard products should be fitted to a plumb surface that is clean, dry, smooth and free from dust, grease and flaking paint. It can be fitted over existing tiles, fair-faced brickwork, blockwork, plaster walls and boarded-out stud partitions. The sheets fix directly to the dry substrate using high quality AM-Clad trade adhesives. See the AM-Clad Installation Guide for full details.

CUTTING AND DRILLING

Sheets can be cut to size using a fine-toothed, circular or jig saw and specialist hand tools. Use slow machine/drill speeds to prevent overheating.

METHOD OF FIXING

Systems and sheets should be bonded to the wall with AM-Clad trade adhesive.

JOINTS

Sheets are fixed using matching PVC 'H-Divider' joints and end trims, flush hot welded joints, or matching foodsafe silicone sealant. Always leave an expansion gap of 3mm to 4mm at all joints/fixings – see current Datasheet and Fixing Detail PDFs for guidance.

CORNERS

Sheets can be expertly thermoformed on-site ensuring a professional finish and minimising edge joints around corners, windows and doors.

FLOOR JUNCTION

Specialist PVC profiles create a neat interface between AM-Guard sheets and floor detail, or a vinyl overlay, as required.

CHEMICAL RESISTANCE

High resistance to mineral acids, alkalis, plating solutions, paper making chemicals, pickling solutions, inorganic solutions and fumes. See individual Datasheets for more details.

FIRE RATINGS

AM-Guard products have been independently tested to the following classifications.

Standard:	Classification:
EN 13501	B, s3, d0
BS 476 Part 6	Class 0
BS 476 Part 7	Class 1

CLEANING

Regular cleaning using a soft cloth and a suitably diluted mild detergent is all that is normally required. Do not use abrasive pads or wire wool. Do not clean above 60°C.

WARRANTY

AM-Guard systems are guaranteed for 30 years. Full Warranty details are available on request.

STORAGE

Sheets should be stored away from direct sunlight at a temperature within a 13°C to 40°C range.

LIMITATIONS

AM-Guard should not be used in rooms where the temperature exceeds 60°C or near a naked flame.

ACCREDITATIONS



APPROVED AM-CLAD INSTALLERS

AM-Clad has a network of approved installers throughout the UK and Ireland. Details available on request.



Contact AM-Clad today for expert advice on specifying and installing our premium quality PVC cladding systems.

Email info@am-clad.com

Call AM-Clad on 01274 020 331

Web AM-CLAD.COM

AM-Clad 10-14 Ward Street, Bradford, West Yorkshire, United Kingdom BD7 3PR